

By Kumari priyadarshani

Date -25-04-2020

BBM 3rd year.

C Identifiers

C identifiers represent the name in the C program, for example, variables, functions, arrays, structures, unions, labels, etc.

An identifier can be composed of letters such as uppercase, lowercase letters, underscore, digits, but the starting letter should be either an alphabet or an underscore. If the identifier is not used in the external linkage, then it is called as an internal identifier. If the identifier is used in the external linkage, then it is called as an external identifier.

We can say that an identifier is a collection of alphanumeric characters that begins either with an alphabetical character or an underscore, which are

used to represent various programming elements such as variables, functions, arrays, structures, unions, labels, etc. There are 52 alphabetical characters (uppercase and lowercase), underscore character, and ten numerical digits (0-9) that represent the identifiers. There is a total of 63 alphanumerical characters that represent the identifiers.

Rules for constructing C identifiers

The first character of an identifier should be either an alphabet or an underscore,

and then it can be followed by any of the character, digit, or underscore.

It should not begin with any numerical digit.

In identifiers, both uppercase and lowercase letters are distinct. Therefore, we can say that identifiers are case sensitive.

Commas or blank spaces cannot be specified within an identifier.

Keywords cannot be represented as an identifier.

The length of the identifiers should not be more than 31 characters.

Identifiers should be written in such a way that it is meaningful, short, and easy to read.

Example of valid identifiers

total, sum, average, `_m_`, `sum_1`, etc.

Example of invalid identifiers

2sum (starts with a numerical digit)

int (reserved word)

char (reserved word)

m+n (special character, i.e., '+')

Types of identifiers

Internal identifier

External identifier

Internal Identifier

If the identifier is not used in the external linkage, then it is known as an internal identifier. The internal identifiers can be local variables.

External Identifier

If the identifier is used in the external linkage, then it is known as an external identifier. The external identifiers can be function names, global variables.

Differences between Keyword and Identifier

Keyword Identifier

Keyword is a pre-defined word. The identifier is a user-defined word

It must be written in a lowercase letter.

It can be written in both lowercase and uppercase letters.

Its meaning is pre-defined in the c compiler. Its meaning is not defined in the c compiler.

It is a combination of alphabetical characters. It is a combination of alphanumeric characters.

It does not contain the underscore character. It can contain the underscore character.

Let's understand through an example.

```
int main()  
{  
    int a=10;
```



```
int A=20;

printf("Value of a is : %d",a);

printf("\nValue of A is :%d",A);

return 0;

}
```

Output

Value of a is : 10

Value of A is :20

The above output shows that the values of both the variables, 'a' and 'A' are different. Therefore, we conclude that the identifiers are case sensitive.

Thank you?

